

SERRATED SAFETY WASHERS - S SERIES LIGHT LOAD

HEGONG Part No.	D(mm)	d(mm)	t(mm)	Hmax(mm)	Hmin(mm)
SW-S-M1.6	3.2	1.7	0.35	0.6	0.38
SW-S-M2	4	2.2	0.35	0.6	0.39
SW-S-M2.5	4.8	2.7	0.45	0.9	0.49
SW-S-M3	5.5	3.2	0.45	0.9	0.51
SW-S-M3.5	6	3.7	0.45	0.9	0.52
SW-S-M4	7	4.3	0.5	1	0.59
SW-S-M5	9	5.3	0.5	1.1	0.73
SW-S-M6	10	6.4	0.7	1.2	0.82
SW-S-M6.35	9.5	6.7	0.7	1.2	0.79
SW-S-M7	12	7.4	0.7	1.3	0.89
SW-S-M8	13	8.4	0.8	1.4	0.98
SW-S-M10	16	10.5	1	1.6	1.21
SW-S-M11.1	15.9	11.6	1	1.6	1.18
SW-S-M12	18	13	1.1	1.7	1.31
SW-S-M12.7	19	13.7	1.1	1.8	1.33
SW-S-M14	22	15	1.2	2	1.52
SW-S-M16	24	17	1.3	2.1	1.63
SW-S-M18	27	19	1.5	2.3	1.85
SW-S-M19	30	20	1.5	2.5	1.98
SW-S-M20	30	21	1.5	2.5	1.94
SW-S-M22	33	23	1.5	2.7	2.08
SW-S-M24	36	25.6	1.8	2.9	2.32
SW-S-M25.4	38	27	2	3.1	2.52
SW-S-M27	39	28.6	2	3.1	2.52
SW-S-M30	45	31.6	2	3.6	2.78
SW-S-M33	50	34.6	2.5	4	3.26
SW-S-M36	54	38	2.5	4.2	3.38

SERRATED SAFETY WASHERS - VS SERIES REINFORCE LOAD

Part No.	D(mm)	d(mm)	t(mm)	Hmax(mm)	Hmin(mm)
SW-VS-M5	9	5.3	1	1.3	1.07
SW-VS-M6	10	6.4	1	1.4	1.08
SW-VS-M8	13	8.4	1.2	1.7	1.32
SW-VS-M10	16	10.5	1.5	2	1.64
SW-VS-M12	18	13	1.5	2.1	1.65
SW-VS-M14	22	15	1.5	2.2	1.76
SW-VS-M16	24	17	2	2.6	2.21
SW-VS-M18	27	19	2	2.7	2.27
SW-VS-M20	30	21	2	2.8	2.34
SW-VS-M22	33	23	2	3	2.42
SW-VS-M24	36	25.6	2.5	3.4	2.87
SW-VS-M4	38	27	2.5	3.4	2.95
SW-VS-M27	39	28.6	2.5	3.5	2.91
SW-VS-M30	45	31.6	2.5	3.8	3.12
SW-VS-M33	50	34.6	3	4.5	3.65
SW-VS-M36	54	38	3	4.5	3.72